

The Superflat bathroom drain



Article information

Item no.: 42701.54
 GTIN: 4026092029626
 Price group: 10

Advantages

- Movable outlet socket
- Lip seal fixed on the drain body
- Side inlet via odour trap

Description

The Superflat bathroom drain is suitable for indoor floor drainage. The drain made of PP is equipped with a secure, reliably installed seal as well as a removable odour trap.

Variant

Sealing water height: 30 mm
 Discharge rate (l/s) with 20 mm backwater: 0,8

General characteristics

Nominal size (DN): 50
 Outer diameter (OD): 50 mm

Dimensions

Vertical adjustment: 10 - 23 mm
 Net weight: 1,85 kg
 Gross weight: 2,09 kg
 Cutout dimension, width: 180 mm
 Cutout dimension, length: 260 mm
 Vertical adjustment: vertically adjustable upper section
 Length: 312 mm
 Width: 312 mm
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Tank/drain body

Number of outlets: 1
 Inlet nominal size (DN): 40 mm
 Inlet type: 1
 Material of drain body: PP

Coverage features

Type of cover:

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Surface:

Frame material:

Cover locking:

Load class:

Grating colour:

Rim length:

Rim material:

Shape of upper section:

Upper section material:

Odour trap:

Design cover

Stainless steel 14301

silver

120 mm

120 mm

ground

Stainless steel 14301

Lock & Lift

K 3 (EN 1253-1)

Oval

132 mm

132 mm

square

PP

included