

Aqualift F XL, 200 L lift. stat. Duo, SPF 4500-S1, 2 shut-off valves



Article information

Item no.: 11122 GTIN: 4026092057896 Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant Type of system:	duo pump
Shut-off valve:	2 shut-off valves made of cast iron
Backflow preventer:	integrated
Pressure pipe connection:	vertical
General characteristics	
Colour:	black
Standard:	EN 12050-1
Type of wastewater:	with sewage
Installation situation:	free-standing installation
System type:	Duo
Dimensions	
Net weight:	202,78 kg
Gross weight:	222,78 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Tank volume:	200 l
Pumping device	



Pump: Number of pumps: Operating voltage: Operating mode: Impeller type: Free passage: Length of mains cable for pump:

Control Control unit: Level measurement instrument: Type of level measurement: Mains frequency: Operating voltage: Type of fuse required (control unit): SPF 4500-S1 2 400 V S1 Multi-vane impeller 40 mm 5 m

Comfort Immersion pipe pneumatic 50 Hz 400 V 3 x C 25 A