


Shell Kit for Pumpfix F, without nozzles, bl.cover





Article information

Item no.: 24000S-RBK GTIN: 4026092097069

Price group: 30

Description

KESSEL shell kit for Pumpfix F, without sockets, black cover

Shell kit consisting of a drain body, upper section and flange for joint sealing. The inlet and outlet sockets are not included.

For combination with a KESSEL technology kit for creating a Pumpfix F backwater pumping station.

General characteristics

Colour: black

Type of wastewater: with sewage

Installation situation: floor slab installation

Delivery state: Pre-mounted for final assembly on site (pumps and

sensor system must be fitted on site and control

unit must be connected)

Approval: Z-53.2-388 Motor type: KSM 140

Type de protection moteur: IP 68 (3m/48h)

Dimensions

Net weight:15,2 kgGross weight:18 kgGroundwater resistant from lower edge of base3000 mm

section:

Cutout dimension, width: 750 mm



Cutout dimension, length: 750 mm
Vertical drop between inlet and outlet: 9 mm

Installation depth: 516 - 669 mm

Type of height adjustability: vertically adjustable upper section

Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Socket version: optional

Coverage features

Type of cover: Cover plate with slotted cover

Cover material:PolymerColour of cover:blackWidth of cover:366 mmLength of cover:366 mmDrainage function:yes

Locking: Lock & Lift
Load class: L 15 (EN 1253-1)

: