


Submersible pump Aquadive GTF1000 resistant, with float switch, 10 m



Article information

Item no.: 28860C
 GTIN: 4026092093771
 Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

Submersible pump for faecal-free wastewater

Variant

Resistant:

Resistant to waste water containing salt, softener and condensate

Pump control:

Float switch

General characteristics

Type of wastewater:

without sewage

Dimensions

Net weight:

10 kg

Gross weight:

10,5 kg

Length:

195 mm

Width:

195 mm

Height:

290 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Pumping device

Pump:	GTF 1000 resistant
Weight, pump:	10 kg
Connection type:	coded plug
Operating voltage:	230 V
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68 (3m)
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,75 kW
Operating mode:	S3 - 50 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Type of fuse required (pump):	C 16 A
Length of mains cable for pump:	10 m
Rated current:	5,6 A
Control	
Type of level measurement:	mechanical
Mains frequency:	50 Hz
Connection type:	coded plug