

Variofix Classic bathroom drain DN 70, horiz., Slotted grating, K 3



Article information

Item no.: 40170.50
GTIN: 4026092029336
Price group: 10

Advantages

- Odour trap height: 50 mm
- Lip seal fixed on the drain body
- Side adjustable cover

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant

| | |
|--|---|
| Waterproofing layer on the upper section: | Enclosed sealing collar to be glued (bd) according to DIN 18534 |
| Waterproofing layer on the drain body: | Adhesive flange (suitable for moisture barriers) |
| Water exposure class in accordance to DIN 18534-1 (up to and including): | W3-I |
| Sealing water height: | 50 mm |
| Discharge rate (l/s) with 20 mm threshold: | 0,8 |

General characteristics

| | |
|----------------------|-----------|
| Standard: | EN 1253-1 |
| Nominal size (DN): | 70 |
| Outer diameter (OD): | 75 mm |
| Odour trap: | included |

Dimensions

| | |
|-------------------------------|-------------------------------------|
| Vertical adjustment: | 45 - 110 mm |
| Net weight: | 0,94 kg |
| Gross weight: | 1,16 kg |
| Cutout dimension, width: | 180 mm |
| Cutout dimension, length: | 220 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Length: | 312 mm |
| Width: | 312 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |

| | |
|-------------------------|-----------------------|
| Packaging dimension: | height |
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | ABS |
| Socket version: | lateral |
| Coverage features | |
| Type of cover: | Slotted cover |
| Cover material: | Stainless steel 14301 |
| Colour of cover: | silver |
| Width of cover: | 95 mm |
| Length of cover: | 95 mm |
| Surface: | Polished SST |
| Frame material: | ABS |
| Locking: | placed |
| Load class: | K 3 (EN 1253-1) |
| Rim width: | 132 mm |
| Rim length: | 132 mm |
| Shape of upper section: | square |
| Upper section material: | ABS |