


## The Ultraflat 79 floor drain DN 50, Des grating, Lock & Lift



### Article information

Item no.: 44700.63  
 GTIN: 4026092080917  
 Price group: 10

### Advantages

- Low installation depth
- Scientifically confirmed sound insulation effect
- different design covers

### Description

The Ultraflat 79 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section.

#### Variant

System:	125
Seepage opening:	optional
Sealing water height:	50 mm
Discharge rate (l/s) with 10 mm threshold:	0,9
Discharge rate (l/s) with 20 mm threshold:	1,1

#### General characteristics

Standard:	EN 1253-1
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Odour trap:	included
Sustainable:	through the use of recycled material

#### Dimensions

Vertical adjustment:	95 - 145 mm
Net weight:	0,88 kg
Gross weight:	0,93 kg
Type of height adjustability:	vertically adjustable upper section
Length:	227 mm
Width:	163 mm
Height:	79 mm

Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS
Socket version:	lateral
Coverage features	
Type of cover:	Design cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Width of cover:	120 mm
Height of cover:	16 mm
Length of cover:	120 mm
Min. flooring height:	9 mm
Surface:	ground
Frame material:	Stainless steel 14301
Locking:	Lock & Lift
Load class:	L 15 (EN 1253-1)
Grating design:	Kessel
Slip resistance class:	R9 according to DIN 51130; C according to DIN 51097
Rim width:	132 mm
Rim length:	132 mm
Max. flooring height:	62 mm
Shape of upper section:	square
Upper section material:	ABS