


## The Ultraflat 54 floor drain DN 50, enclWPM, Des grating, Lock&Lift



## **Article information**

Item no.: 44750.63 GTIN: 4026092080870

Price group: 10

## **Advantages**

- including removable odour trap in the upper section
- Low installation depth
- Scientifically confirmed sound insulation effect

## **Description**

The Ultraflat 54 floor drain is suitable for indoor floor drainage. The polymer drain is equipped with a removable odour trap in the upper section. Open seepage water opening, no flooding of the waterproofing level in the event of build-up.

Variant

System: 125 Seepage opening: optional

Waterproofing layer on the drain body: Enclosed sealing collar to be glued (bd) according to

DIN 18534

W2-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 22 mm

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 50 mm
Odour trap: included

Sustainable: through the use of recycled material

**Dimensions** 

Vertical adjustment:70 - 121 mmNet weight:0,87 kgGross weight:1,02 kg

Type of height adjustability: vertically adjustable upper section

Length: 246 mm
Width: 200 mm
Height: 54 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height



Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301

Colour of cover:silverWidth of cover:120 mmHeight of cover:16 mmLength of cover:120 mm

Frame material: Stainless steel 14301

Locking: Lock & Lift
Load class: L 15 (EN 1253-1)

Grating design:

Rim width:

Rim length:

Shape of upper section:

Upper section material:

Kessel

132 mm

132 mm

square

ABS