


Practicus drain body DN 100, Vertical outlet



Article information

Item no.: 45210
 GTIN: 4026092033593
 Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Variant

| | |
|---|-------------------|
| System: | 125 |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body: | Connection flange |
| Sealing water height: | 50 mm |

General characteristics

| | |
|----------------------|---|
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 110 mm |
| Approval: | Z-19.53-2414,Z-19.53-2414_V,Z-19.17-1719,Z-19.17-1719_V |
| Odour trap: | included |

Dimensions

| | |
|---------------|---------|
| Net weight: | 0,74 kg |
| Gross weight: | 0,85 kg |
| Diameter: | 135 mm |
| Height: | 201 mm |

| | |
|-------------------------|----------|
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | PP |
| Socket version: | vertical |