


Shower chan. Linearis Infinity 60 L: 1200 mm, DN 40, Br. Bronze, Megastop





Article information

Item no.: 45304.12 GTIN: 4026092094624

Price group: 10

Advantages

- Channel profile made of 316 stainless steel
- Including Sound and settlement absorbers
- No flooding of the waterproofing level in the event of water build-up

Description

The narrow Linearis Infinity channel for walk-in showers is suitable for indoor linear drainage for household and commercial use. The narrow Linearis Infinity channel for walk-in showers is suitable for indoor linear drainage for household and commercial use. The channel profile made of 316 stainless steel can be extended straight or at three (30, 45 and 90 degree) angles. The drain body made of PP is equipped with sound and settlement absorbers. These reduce operating noise and can compensate for subsidence in the floor structure. The channel contains a clip-on flange with a factory-mounted waterproofing membrane according to DIN EN 1253-1 and DIN 18534-1-W3-I. The channel profile can be pushed in the lengthwise and transverse direction in the clip-on flange to compensate for construction tolerances. Including Megastop mechanical odour trap with water seal. Open seepage water openings, without flooding of the waterproofing level in the event of build-up.

Variant

Water exposure class in accordance to DIN W3-I

18534-1 (up to and including):

Discharge rate (l/s) with 10 mm threshold: 0,2 Discharge rate (l/s) with 20 mm threshold: 0,4

General characteristics

Nominal size (DN): 40



Odour trap: Megastop

Dimensions

Net weight: 3,45 kg Gross weight: 3,45 kg Min. design height: 60 mm Vertically adjustable: ves Length: 264 mm Width: 111 mm Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Outlet nominal size (OD):

Outlet nominal size (DN):

Material of drain body:

Socket version:

40 mm

PP

lateral

Coverage features

Type of cover: Stainless steel cover Cover material: 316 stainless steel

Width of cover: 45 mm
Length of cover: 1200 mm
Min. flooring height: 11 mm

Surface: Bronze brushed

Locking: placed

Load class: K 3 (EN 1253-1)

Max. flooring height: 25 mm Shape of upper section: square