


## Shower channel Linearis Compact L: 850 mm, DN 50, WaD, 304 SST cov., K 3





## **Article information**

Item no.: 45600.64M GTIN: 4026092078921

Price group: 10

## **Advantages**

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

## **Description**

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

Variant

System: 125

Seepage opening: prepared

Waterproofing layer on the upper section: Factory-fitted sealing collar (WaD) according to DIN

18534 W3-I

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height:

Discharge rate (l/s) with 10 mm threshold:

Discharge rate (l/s) with 20 mm threshold:

O,6

Discharge rate (l/s) with 20 mm threshold:

O,7

Discharge rate (l/s) without threshold:

O,5 mm

General characteristics

Nominal size (DN): 50
Outer diameter (OD): 50 mm
Odour trap: included

**Dimensions** 



Net weight: 2,28 kg Gross weight: 2,8 kg Outer dimension, length: 915 mm Installation depth: 80 - 140 mm Width: 191 mm 80 mm Height: Packaging dimension: length Packaging dimension: width Packaging dimension: height

Tank/drain body

Number of outlets: 1
Material of drain body: ABS

Coverage features

Type of cover: Stainless steel cover Cover material: Stainless steel 14301

Colour of cover: silver

Frame material: Stainless steel 14301

Load class: K 3 (EN 1253-1)
Grating design: optionally tileable

Rim width: 66 mm
Rim length: 850 mm
Max. flooring height: 15 mm
Upper section material: ABS