

## Roof drain Ecoguss Press. fl., DN 100, with heating



## **Article information**

Item no.: 48310.03 GTIN: 4026092039267 Price group: 40

## **Advantages**

- Made of recyclable composite
- Permanently corrosion-free surface

Please consult the KESSEL Service Centre for

trapezoidal roof areas greater than 2500 sqm.

## Description

The Ecoguss roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. Separate equipotential bonding is not necessary. Note:

> 200 with Press sealing flange (suitable for creating watertight seals)

General characteristics Standard: Nominal size (DN): Outer diameter (OD):

Waterproofing layer on the drain body:

Dimensions Net weight: Gross weight: Diameter:

Variant

System: Heating:

Subject to technical changes.

EN 1253 100

110 mm

5,25 kg

5,46 kg

365 mm



Cutout dimension, width: Cutout dimension, length: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Material of drain body:

Coverage features Type of cover: Cover material: Colour of cover: Shape of upper section: Upper section material: 227 mm 227 mm 365 mm 365 mm length width height

Ecoguss

Gravel trap Polymer black round Ecoguss