

## Roof drain Ecoguss Press. fl., DN 125, without heating



## **Article information**

Item no.: 48312

GTIN: 4026092039274

Price group: 40

## **Advantages**

- Made of recyclable composite
- Permanently corrosion-free surface

## **Description**

The Ecoguss roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. Separate equipotential bonding is not necessary. Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

Variant

System: 200 Heating: without

Waterproofing layer on the drain body: Press sealing flange (suitable for creating

watertight seals)

General characteristics

Standard:EN 1253Nominal size (DN):125Outer diameter (OD):125 mm

Dimensions

Net weight:2,56 kgGross weight:3,17 kgDiameter:365 mm



Cutout dimension, width:

Cutout dimension, length:

Length:

Width:

Packaging dimension:

Tank/drain body

Material of drain body: Ecoguss

Coverage features

Type of cover: Gravel trap
Cover material: Polymer
Colour of cover: black
Upper section material: Ecoguss