



Variofix upper section tileable, 304 st., K 3



Article information

Item no.: 48906
GTIN: 4026092029756
Price group: 10

Advantages

- Different covers selectable
- Including waterproofing membrane

Description

Used in combination with a drain body of the KESSEL modular system, the upper section is suitable for indoor point drainage.

Variant

System:

Waterproofing layer on the upper section:

Water exposure class in accordance to DIN 18534-1 (up to and including):

125

Enclosed sealing collar to be glued (bd) according to DIN 18534

W3-I

General characteristics

Sustainable:

through the use of recycled material

Dimensions

Vertical adjustment:

10 - 21 mm

Net weight:

1,4 kg

Gross weight:

1,62 kg

Diameter:

312 mm

Type of height adjustability:

vertically adjustable upper section

Height:

120 mm

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Coverage features

Type of cover:	tileable cover plate
Cover material:	tileable
Colour of cover:	selectable
Frame material:	Stainless steel 14301
Locking:	lockable
Load class:	K 3 (EN 1253-1)
Grating design:	optionally tileable
Rim width:	132 mm
Rim length:	132 mm
Upper section:	adjustable in three dimensions
Shape of upper section:	square
Upper section material:	ABS