



Variofix upper section Slotted grating, 304 SST, L 15



Article information

Item no.: 48965
GTIN: 4026092004708
Price group: 70

Advantages

- Different covers selectable
- Including waterproofing membrane

Description

Used in combination with a drain body of the KESSEL modular system, the upper section is suitable for indoor point drainage.

Variant

Seal:

Waterproofing layer on the upper section:

Water exposure class in accordance to DIN 18534-1 (up to and including):

General characteristics

Sustainable:

Lip seal

Enclosed sealing collar to be glued (bd) according to DIN 18534

W3-I

through the use of recycled material

Dimensions

Vertical adjustment:

Net weight:

Gross weight:

Diameter:

Type of height adjustability:

Height:

Packaging dimension:

Packaging dimension:

Packaging dimension:

23 - 40 mm

2,4 kg

2,64 kg

312 mm

vertically adjustable upper section

120 mm

length

width

height

Coverage features

Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Surface:	pickled
Frame material:	Stainless steel 14301
Locking:	placed
Load class:	L 15 (EN 1253-1)
Grating design:	Cross
Rim width:	150 mm
Rim length:	150 mm
Upper section:	adjustable in three dimensions
Shape of upper section:	square
Upper section material:	ABS
Mesh size:	23 x 23 mm