


Drain body Ferrofix DN100,vertical,with OT and sludge bucket



Article information

Item no.: 55100
GTIN: 4026092107492
Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- Variably combinable with upper sections

Description

In combination with a System 185 upper section, the Ferrofix stainless steel drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The outlet socket is suitable for connection to SML cast iron pipes. With a drainage capacity ■ 2.4 l/s with 20 mm build-up

| | |
|--|-------------------|
| Variant | |
| System: | 185 |
| Waterproofing layer on the drain body: | Connection flange |
| Sealing water height: | 50 mm |

| | |
|-------------------------|-----------|
| General characteristics | |
| Standard: | EN 1253-1 |
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 201 mm |
| Odour trap: | included |

| | |
|----------------------|--------|
| Dimensions | |
| Net weight: | 5 kg |
| Gross weight: | 5 kg |
| Width: | 260 mm |
| Height: | 230 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

| | |
|-------------------------|-----------------------|
| Tank/drain body | |
| Number of outlets: | 1 |
| Material of drain body: | Stainless steel 14301 |
| Socket version: | vertical |