



Drain body glued flange DN100, horizontal, w. OT and sludge bucket



Article information

Item no.: 55125
GTIN: 4026092107546
Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- Variably combinable with upper sections

Description

In combination with a System 185 upper section, the Ferrofix stainless steel drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The glued flange with a flange width of 50 mm is suitable for connecting waterproofing layers in accordance with DIN 18534, for all waterproofing classes. The outlet socket is suitable for connection to SML cast iron pipes. With a drainage capacity ■ 2.4 l/s with 20 mm build-up.

Variant

System:	185
Waterproofing layer on the drain body:	Adhesive flange (suitable for moisture barriers)
Sealing water height:	50 mm

General characteristics

Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	201 mm
Odour trap:	included

Dimensions

Net weight:	6,65 kg
Gross weight:	6,65 kg
Width:	404 mm
Height:	180 mm
Packaging dimension:	length
Packaging dimension:	width

Packaging dimension:

height

Tank/drain body

Number of outlets:

1

Material of drain body:

Stainless steel 14301

Socket version:

lateral