

## Pump drive SPF 3000 400 V, S1, 10 m cable



### Article information

Item no.: 680532  
 GTIN: 4026092074930  
 Price group: 90

### Description

Pump drive type SPF 3000-S1 for Aqualift F XL pumping station, dry installation

#### Dimensions

|                      |         |
|----------------------|---------|
| Net weight:          | 27,5 kg |
| Gross weight:        | 30,3 kg |
| Packaging dimension: | length  |
| Packaging dimension: | width   |
| Packaging dimension: | height  |

#### Pumping device

|  |  |
|--|--|
| Pump:  | SPF 3000-S1                                |
| Connection type:                                   | Direct connection                          |
| Operating voltage:                                 | 400 V                                      |
| Mains frequency:                                   | 50 Hz                                      |
| Protection class:                                  | I  |
| Insulation class:                                  | F  |
| Cos phi - power factor:                            | 0,89                                       |
| Protection class (pump):                           | IP 68                                      |
| Max. temperature (permanent) of conveyed material: | 40 °C                                      |
| Max. pumping height:                               | 16 m                                       |
| Speed:   | 2845 U/min                                 |
| Power P1:  | 3,2 kW                                     |
| Power P2:  | 2,7 kW                                     |
| Operating mode:                                    | S1   |
| Type of pump connection cable:                     | H07RN-F 7G 1.5 mm <sup>2</sup>             |
| Type of fuse required (pump):                      | Fuse protection through control unit 400 V |
| Rated current:                                     | 5,4 A                                      |

#### Control

|                    |                   |
|--------------------|-------------------|
| Operating voltage: | 400 V             |
| Connection type:   | Direct connection |