

## Replacement pump Aquadive SPF1300 230 V



### Article information

Item no.: 680535  
 GTIN: 4026092075012  
 Price group: 90

### Description

Replacement pump, Aquadive, SPF 1300 for faecal wastewater

Variant	
Pump control:	Control unit
General characteristics	
Type of wastewater:	with sewage
Dimensions	
Net weight:	9,39 kg
Gross weight:	10,3 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	SPF 1300
Number of pumps:	1
Weight, pump:	9,39 kg
Connection type:	Direct connection
Operating voltage:	230 V
Mains frequency:	50 Hz
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,98
Protection class (pump):	IP 68
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Max. pumping height:	9,2 m
Speed:	2600 U/min
Power P1:	1,5 kW
Power P2:	0,91 kW

Operating mode:	S3 - 10 %
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Length of mains cable for pump:	5 m
Rated current:	6,4 A
Control	
Operating voltage:	230 V
Connection type:	Direct connection