

Replacement pump Aquadive GTF1200 without float switch, 10 m



Article information

Item no.: 680595
 GTIN: 4026092078815
 Price group: 90

Description

Replacement pump, Aquadive GTF 1200 without floater for pumping station

Variant	
Pump control:	Control unit
General characteristics	
Cable length:	10 m
Dimensions	
Net weight:	11,19 kg
Gross weight:	11,19 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	GTF 1200
Connection type:	Schuko (earthed contact) 2-pin
Operating voltage:	230 V
Mains frequency:	50 Hz
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,98
Protection class (pump):	IP 68
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Max. pumping height:	9 m
Speed:	2650 U/min
Power P1:	1,4 kW
Power P2:	0,84 kW
Operating mode:	S1
Type of pump connection cable:	H07RN-F 3G 1.5 mm²

Type of fuse required (pump):
Length of mains cable for pump:
Rated current:

Fuse protection through control unit 230 V
5 m
6,2 A

Control
Operating voltage:
Connection type:

230 V
Schuko (earthed contact) 2-pin