
IK KESSEL

Staufix clean out DN 125, Floor slab, black





Article information

Item no.: 700125.10S GTIN: 4026092075920 Price group: 10

Advantages

- Simple conversion to Staufix type 1
- Own gradient only 8 mm
- Quick and toolless access for cleaning

Description

The clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work. Thanks to the modular KESSEL system, existing systems can easily be supplemented by up to two flaps and one emergency closure or be converted to the StaufixControl backwater valve.

General characteristics	black
Colour:	125
Nominal size (DN):	125 mm
Outer diameter (OD):	for wastewater with and without sewage
Type of wastewater:	floor slab installation
Installation situation:	Installation-ready (connection parts must be
Delivery state:	connected on site)
Dimensions Net weight: Gross weight: Groundwater resistant from lower edge of base section: Cutout dimension, width: Cutout dimension, length: Vertical drop between inlet and outlet: Installation depth: Type of height adjustability:	8 kg 10,6 kg 3 mm 750 mm 750 mm 8 mm 341 - 464 mm vertically adjustable upper section



Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Locking: Load class: Tightness: 511 mm 444 mm length width height

Cover plate Polymer black 366 mm 366 mm Lock & Lift L 15 (EN 1253-1) surface water resistant