


Backwater valve Staufix DN 150, exposed, Type 1



Article information

Item no.: 720150
GTIN: 4026092076088
Price group: 10

Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

Variant

| | |
|-----------------------------|-----|
| Emergency closure: | yes |
| Mechanical backwater flaps: | 1 |

General characteristics

| | |
|-------------------------|-----------------------|
| Colour: | black |
| Standard: | EN 13564 |
| Nominal size (DN): | 150 |
| Outer diameter (OD): | 160 mm |
| Type of wastewater: | without sewage |
| Installation situation: | exposed drainage pipe |
| Delivery state: | installation-ready |
| Backwater protection: | Type 1 |

Dimensions

| | |
|---------------|---------|
| Net weight: | 3,2 kg |
| Gross weight: | 3,97 kg |

| | |
|---|--------------------|
| Vertical drop between inlet and outlet: | 8 mm |
| Length: | 523 mm |
| Width: | 216 mm |
| Height: | 306 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| Coverage features | |
| Type of cover: | Lockable cover |
| Cover locking: | One-handed closure |