


## Backwater valve Staufix SWA DN 125, exposed





## **Article information**

Item no.: 73125.10 GTIN: 4026092003930

Price group: 30

## **Advantages**

- Simple conversion to Staufix FKA or Pumpfix F
- Fast, simple and toolless maintenance
- Available as a complete set or module set

## **Description**

The premium backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves at the same time as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to a Staufix FKA premium backwater valve or a Pumpfix F backwater pumping station.

Variant

Emergency closure: yes Mechanical backwater flaps: 2

General characteristics

Colour: black
Standard: EN 13564
Nominal size (DN): 125

Outer diameter (OD): 125 mm

Type of wastewater: without sewage
Installation situation: exposed drainage pipe
Delivery state: installation-ready

Backwater protection: Type 2

**Dimensions** 

Net weight: 11,1 kg
Gross weight: 12 kg
Vertical drop between inlet and outlet: 9 mm
Length: 645 mm



Width: 350 mm
Height: 422 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Socket version: including spigot and socket

Coverage features

Type of cover: Protective cover

Cover material:PolymerColour of cover:transparentWidth of cover:350 mmHeight of cover:165 mmLength of cover:542 mmLocking:Clip closure