

Yard drain System 400, DN 100, A, 380 - 510 mm



Article information

Item no.: 851100A GTIN: 4026092004258

Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals. The polymer upper section enables continuous height and level adjustment.

Variant

System: 400
Heating: without
Contents of sludge trap: yes
Discharge rate (l/s) with 20 mm threshold: 4,5

General characteristics

Colour: black
Standard: EN 752
Nominal size (DN): 100
Outer diameter (OD): 110 mm
Odour trap: no

Dimensions

Net weight: 10 kg
Gross weight: 10 kg
Groundwater resistant from lower edge of base 500 mm

section:

Cutout dimension, width: 535 mm
Cutout dimension, length: 585 mm
Min. insertion depth: 55 mm
Installation depth: 380 - 510 mm

Type of height adjustability: vertically adjustable upper section

Packaging dimension: length
Packaging dimension: width
Packaging dimension: height



Tank/drain body

Number of outlets:

Material of drain body: Polymer Socket version: lateral

Coverage features

Type of cover: Round slotted cover

Cover material:

Colour of cover:

Width of cover:

Length of cover:

Surface:

Polymer

400 mm

400 mm

EDM

Load class:A 15 (EN 124)Rim width:400 mmRim length:400 mmShape of upper section:squareContents of sludge trap:yes