

## Upper Section LW 600 Begu, height-adjustable 79 - 579 mm





## Article information

Item no.: 860154 GTIN: 4026092102503 Price group: 60

## **Description**

Upper section with clamping ring suitable for chamber systems LW 1000/800/600 for covers resistant to surface water, class A/B or D, with Lock & Lift, continuously height-adjustable by 514 mm (Comfort and engineering chamber system) or 400 mm (standard chamber system).

If installed in roads, parking areas and comparable hard-surfaced traffic areas for trucks (Class D), the upper section must be underlaid on site with a reinforced supporting slab made of concrete. A standard formwork and reinforcement drawing can be provided.

Access steps (art. no. 860109) must be installed if the allowable difference between the top of the chamber cover and the first step is exceeded.

| Minimum insertion depth: | 80 mm (Comfort and engineering chamber system)<br>or 94 mm (standard chamber system and cisterns). |
|--------------------------|--|
| Dimensions               |  |
| Net weight:              | 16,39 kg   |
| Gross weight:            | 16,39 kg   |
| Diameter:                | 850 mm   |
| Adjustment range:        | 79 - 579   |
| Height:                  | 659 mm   |
| Packaging dimension:     | length   |
| Packaging dimension:     | width  |
| Packaging dimension:     | height   |
|                          |  |



Coverage features Cover material: Colour of cover:

PP black