


## Chamber module LW 1000 floor slab Access LW 800, 2911-3160 mm, Class K 3



### Article information

Item no.: 8740062  
 GTIN: 4026092065778  
 Price group: 60

### Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

### Description

The chamber module for wet installation is equipped with all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, a taper, upper section and cover.

#### General characteristics

Colour:	black
Material:	PE-HD
Standard:	EN 13598-2
Installation situation:	floor slab installation
Delivery state:	Partly for on-site assembly (access steps have been pre-mounted in the factory)
Approval:	Z-42.1-527
Tightness:	surface water resistant

#### Dimensions

Net weight:	226,01 kg
Gross weight:	265,45 kg

Groundwater resistant from lower edge of base section:	3000 mm
Installation depth:	2911 - 3160 mm
Type of height adjustability:	vertically adjustable upper section
Length:	1200 mm
Width:	1200 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Inlet max. scoring (DN):	150
Clear width of tank (LW):	1000 mm
Clear width of entry (LW):	800 mm
Coverage features	
Type of cover:	Rectangular cover plate
Cover material:	Stainless steel
Width of cover:	860 mm
Height of cover:	79 mm
Length of cover:	860 mm
Surface:	tileable
Locking:	screwed
Load class:	K 3 (EN 1253-1)
Tightness:	surface water resistant
Max. flooring height:	14 mm