

## Chamber module LW 1000 floor slab Access LW 800, 1388-1637 mm, K 3, wa.co.



### Article information

Item no.: 8740225  
GTIN: 4026092093238  
Price group: 60

### Advantages

- For modular assembly with simple connection segments and intermediate sections 250 and 500 mm high
- Innovative honeycomb structure
- Installation in groundwater up to 3000 mm

### Description

The chamber module for wet or dry installation is equipped with fitted access steps in accordance with DIN EN 13101 and BGR 177, all the necessary seals and connecting wedges as well as a taper with vertically adjustable upper section. The intermediate sections made of permanently resistant polymer (PE) have universal connection possibilities. Thanks to the modular KESSEL system, the design can be flexibly combined with intermediate sections, taper, upper section and cover.

#### General characteristics

Colour:	black
Material:	PE-HD
Standard:	EN 13598-2
Installation situation:	floor slab installation
Delivery state:	Partly for on-site assembly (access steps have been pre-mounted in the factory)
Approval:	Z-42.1-527

#### Dimensions

Net weight:	145,29 kg
Gross weight:	165,35 kg
Groundwater resistant from lower edge of base section:	3000 mm
Diameter:	960 mm
Installation depth:	1388 - 1637 mm
Type of height adjustability:	vertically adjustable upper section
Length:	1200 mm
Width:	1200 mm
Packaging dimension:	length
Packaging dimension:	width

Packaging dimension:	height
Tank/drain body	
Inlet max. scoring (DN):	150 mm
Clear width of tank (LW):	1000 mm
Clear width of entry (LW):	800 mm
Coverage features	
Type of cover:	Round cover plate
Cover material:	Stainless steel
Height of cover:	19 mm
Surface:	anti-slip
Locking:	screwed
Load class:	K 3 (EN 1253-1)
Tightness:	surface water resistant