

## Grease separat. EasyClean Modular free, NS 1, Standard, 2-part



## **Article information**

Item no.: 93001 GTIN: 4026092030875 Price group: 60

## **Advantages**

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

## Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant Chamber system: Disposal variant: Shredder-Mix-System: Inspection window: Nominal size (NS): SonicControl: Refill inlet in accordance with DIN 1988:	two-piece chamber Standard no no 1 no no
Type of disposal:	manual with suction hose
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must b connected on site)
Dimensions Net weight: Gross weight: Height tank bottom up to centre section: Height centre section to top edge of tank:	41,5 kg 51 kg 648 mm 340 mm

be



Set-up area, length:	1100 mm
Set-up area, width:	1012 mm
Set-up area, height:	988 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	415 mm
Distance pipe bottom inlet to tank bottom:	485 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
Coverage features	
Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Locking:	Quick-release closure
Tightness:	odour-tight
Wastewater contents	
Separator contents:	100 l
Total volume:	200 l
Contents of sludge trap:	100 l
Storage quantity of grease:	40 l
Control	
Control unit:	ΠΟ