

## Grease separator EasyClean free NS 2, Standard



## **Article information**

Item no.: 93002.01 GTIN: 4026092060872

Price group: 60

## **Advantages**

- Direction of flow can be changed thanks to selfsealing interchangeable hubs
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

## **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Standard Disposal variant: Shredder-Mix-System: no Inspection window: no Nominal size (NS): 2 SonicControl: no Refill inlet in accordance with DIN 1988:

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): F3

General characteristics

PF Material:

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

**Dimensions** 

Net weight: 80 kg Gross weight: 95 kg Set-up area, length: 1736 mm Set-up area, width: 674 mm 1434 mm Set-up area, height:



Required access area, length:

Required access area, width:

Required access area, height:

1434 mm

Packaging dimension:

Packaging dimension:

width

Packaging dimension:

height

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (OD):

Inlet nominal size (DN):

100 mm

Inlet nominal size (DN):

100 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: violet

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents:400 lTotal volume:600 lContents of sludge trap:200 lStorage quantity of grease:100 l

Control

Control unit: no