

## Grease separator EasyClean free NS 4, Direct, Refill inlet, Insp. window



### Article information

Item no.: 93004.31/D  
GTIN: 4026092063699  
Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

#### Variant

|   |                     |
|---|---------------------|
| Disposal variant:                         | Direct              |
| Shredder-Mix-System:                      | no                  |
| Inspection window:                        | yes                 |
| Nominal size (NS):                        | 4                   |
| SonicControl:                             | no                  |
| Disposal system:                          | Disposal connection |
| Refill inlet in accordance with DIN 1988: | yes                 |
| Type of disposal:                         | manual              |
| Load-bearing capacity (DIN 19901):        | F3                  |

#### General characteristics

|                         |   |
|-------------------------|---|
| Material:               | PE  |
| Standard:               | EN 1825   |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |
| Scope of delivery:      | Storz-B coupling R 2 1/2" for disposal vehicle connection       |

## Dimensions

|                               |         |
|-------------------------------|---------|
| Net weight:                   | 100 kg  |
| Gross weight:                 | 125 kg  |
| Set-up area, length:          | 2116 mm |
| Set-up area, width:           | 702 mm  |
| Set-up area, height:          | 1432 mm |
| Required access area, length: | 1880 mm |
| Required access area, width:  | 680 mm  |
| Required access area, height: | 1432 mm |
| Packaging dimension:          | length  |
| Packaging dimension:          | width   |
| Packaging dimension:          | height  |

## Tank/drain body

|   |   |
|---|---|
| Nominal pressure (PN):                      | 10  |
| Pressure pipe connection (DN):              | 65  |
| Pressure pipe connection (OD):              | 75 mm   |
| Distance pipe bottom outlet to tank bottom: | 985 mm  |
| Distance pipe bottom inlet to tank bottom:  | 1055 mm   |
| Outlet nominal size (OD):                   | 110 mm  |
| Outlet nominal size (DN):                   | 100 mm  |
| Inlet nominal size (OD):                    | 110 mm  |
| Inlet nominal size (DN):                    | 100 mm  |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Servicing opening:                          | 420 mm  |

## Coverage features

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Locking:         | Quick-release closure |
| Tightness:       | odour-tight           |

## Wastewater contents

|                             |       |
|-----------------------------|-------|
| Separator contents:         | 400 l |
| Total volume:               | 800 l |
| Contents of sludge trap:    | 400 l |
| Storage quantity of grease: | 160 l |

## Control

|               |    |
|---------------|----|
| Control unit: | no |
|---------------|----|