

## EasyClean round grease separator free, NS 10, Direct



## **Article information**

Item no.: 93010.05/D

GTIN:

Price group: 60

## **Advantages**

- Odour-reduced disposal with the tank closed
- Low-maintenance operation

## **Description**

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for reduced-odour manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

Variant

Shut-off valve: yes
Disposal variant: Direct
Shredder-Mix-System: no
Inspection window: no
Nominal size (NS): 10
SonicControl: no

Disposal system: Disposal connection

Refill inlet in accordance with DIN 1988: no Type of disposal: manual Load-bearing capacity (DIN 19901): F3

General characteristics

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle

connection

**Dimensions** 

Net weight: 350 kg
Gross weight: 350 kg
Set-up area, length: 1900 mm
Set-up area, width: 1690 mm
Set-up area, height: 1910 mm



Required access area, length:

Required access area, width:

Required access area, height:

1900 mm
1690 mm
1910 mm

Tank/drain body

10 Nominal pressure (PN): Pressure pipe connection (DN): 65 Pressure pipe connection (OD): 75 mm Distance pipe bottom outlet to tank bottom: 1500 mm Distance pipe bottom inlet to tank bottom: 1570 mm Outlet nominal size (OD): 160 mm Outlet nominal size (DN): 150 160 mm Inlet nominal size (OD): 150 Inlet nominal size (DN):

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 1500 l
Total volume: 2500 l
Contents of sludge trap: 1000 l
Storage quantity of grease: 400 l

Control

Control unit: no