

EasyClean round grease separator free, NS 15, Direct



Article information

Item no.: 93015.05/D

GTIN:

Price group: 60

Advantages

- Odour-reduced disposal with the tank closed
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for reduced-odour manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

Variant

Shut-off valve: yes
Disposal variant: Direct
Shredder-Mix-System: no
Sludge bucket: no
Nominal size (NS): 15,00
SonicControl: no

Disposal system: Disposal connection

Refill inlet in accordance with DIN 1988: no Type of disposal: manual Load-bearing capacity (DIN 19901): F3

General characteristics

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle

connection

Dimensions

Net weight: 350 kg
Gross weight: 350 kg
Set-up area, length: 2230 mm
Set-up area, width: 1922 mm
Set-up area, height: 2020 mm



Required access area, length:

Required access area, width:

Required access area, height:

2230 mm

2230 mm

2020 mm

Tank/drain body

10 Nominal pressure (PN): Pressure pipe connection (DN): 65 Pressure pipe connection (OD): 75 mm Distance pipe bottom outlet to tank bottom: 1550 mm Distance pipe bottom inlet to tank bottom: 1620 mm Outlet nominal size (OD): 200 mm Outlet nominal size (DN): 200 mm Inlet nominal size (OD): 160 mm 150 mm Inlet nominal size (DN):

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: black

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents: 2300 l
Total volume: 3800 l
Contents of sludge trap: 1500 l
Storage quantity of grease: 600 l

Control

Control unit: no