

## EasyClean round grease separator free, NS 20, Direct



## Article information

Item no.: 93020.05/D GTIN: Price group: 60

## **Advantages**

- Odour-reduced disposal with the tank closed
- Low-maintenance operation

## Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for reduced-odour manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

Variant Shut-off valve: Disposal variant: Shredder-Mix-System: Sludge bucket: Nominal size (NS): SonicControl: Disposal system: Refill inlet in accordance with DIN 1988: Type of disposal: Load-bearing capacity (DIN 19901):	yes Direct no no 20,00 no Disposal connection no manual F3
General characteristics Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection
Dimensions Net weight: Gross weight: Set-up area, length: Set-up area, width: Set-up area, height:	280 kg 360 kg 2230 mm 1922 mm 2300 mm



Required access area, length: Required access area, width: Required access area, height:	2230 mm 1880 mm 2300 mm
Tank/drain body Nominal pressure (PN): Pressure pipe connection (DN): Pressure pipe connection (OD): Distance pipe bottom outlet to tank bottom: Distance pipe bottom inlet to tank bottom: Outlet nominal size (OD): Outlet nominal size (DN): Inlet nominal size (DN): Inlet nominal size (DN): Connection inlet/outlet sockets:	10 65 75 mm 1850 mm 1920 mm 200 mm 200 mm 160 mm 150 mm PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS
Coverage features Type of cover: Cover material: Colour of cover: Locking: Tightness:	Cover Polymer black Quick-release closure odour-tight
Wastewater contents Separator contents: Total volume: Contents of sludge trap: Storage quantity of grease:	2650 l 4650 l 2000 l 800 l
Control Control unit:	no