

EasySink sediment separator ground, NS 2, Class B



Article information

Item no.: 97202/00B GTIN: 4026092026908

Price group: 60

Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank

Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers. 20 year polyethylene warranty. Options:

Hole diameter of sediment tank

Variant

Nominal size (NS): 2,00

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): E2

General characteristics

Material: PE

Installation situation: underground installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Odour trap: included

Dimensions

section:

Net weight: 45 kg
Gross weight: 54 kg
Groundwater resistant from lower edge of base 500 mm

Installation depth: 55 - 405 mm

Type of height adjustability: vertically adjustable upper section, can be tilted by

5 degrees



Required access area, length:

Required access area, width:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Packaging dimension:

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (OD):

110 mm

Inlet nominal size (DN):

100 mm

Inlet nominal size (DN):

100 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, PVC-KG

pipes in accordance with DIN 19534, PP or AS

Clear width of entry (LW): 400 mm Volume of collecting tank: 32 l

Coverage features

Type of cover:

Cover material:

Colour of cover:

Width of cover:

Height of cover:

Length of cover:

Cover plate

Grey iron

black

364 mm

4 mm

Locking:

Locked

Load class: B 125 (EN 124)

Tightness: odour-tight and surface water resistant

Control

Control unit: no